

Certificate of Conformity

Certificate: 13047-1G Master Contract: LC 787924

Project: 13047 Date Issued: May 30, 2017

Issued to: Pacific Energy Fireplace Products, Ltd.

2975 Allenby Road Duncan, British Columbia V9L 6V8, Canada Certification System Type 3 (ISO / IEC Guide 67)

The products listed below are eligible to bear the LabTest Certification Mark with adjacent indicators 'C' and 'US', and the subject area as shown below.



Issued by:

Certification Manager

PRODUCTS

Direct Vented Gas Fireplaces:

3FT Architectural Series

- Maximum Input Rating: 48,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

4FT Architectural Series

- Maximum Input Rating: 64,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

5FT Architectural Series

- Maximum Input Rating: 80,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

6FT Architectural Series

- Maximum Input Rating: 96,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

7FT Architectural Series

- Maximum Input Rating: 112,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

8FT Architectural Series

- Maximum Input Rating: 128,000 BTU/hr (Natural Gas or Propane)
- Electrical Ratings: 115VAC / 5.9A / 60HZ

APPLICABLE REQUIREMENTS & SUBJECT AREA

> ANSI Z21.50-(2016) / CSA 2.22-(2016) Vented Decorative Gas Appliances

CONDITIONS OF ACCEPTABILITY

- Suitable for use with Natural Gas or Propane, for indoor use only.
- Not to be used with solid fuel.
- > Suitable for use in high altitudes per: CAN/CGA 2.17-M91 Gas Appliances for Use at High Altitudes

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable Standards respectively. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.