

Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Product Type 1 Label

 Evaluated to/Évalué pour: AAMA/WDMA/CSA 101/I.S.2/A440-17 CSA A440S1:19	Manufacturer: Polishinterior S.C. Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland Email: maciek@polishinterior.com Tel: +48 502 24 88 94 Model No: PI-RSL38F-IG01 RSL38F Fixed Window Class CW – PG40 – Size tested: 1525 x 2515 mm (~60 x 99 in) – Type FW Positive/ Negative ASD Design Pressure (DP) = 1920 Pa Water Penetration Resistance Test Pressure = 290 Pa Canadian Air Infiltration/ Exfiltration = Fixed Level
--	--

Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Polishinterior S.C. Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland Email: maciek@polishinterior.com Tel: +48 502 24 88 94							
Energy Performance Results for RSL38F Fixed Window – PI-RSL38F-IG01 PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.039$, S3), Spacer: Multitech G ALU PRO Warm Edge Spacer							
No. of glazing layers	Glazing option no.	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	01*	CG Prem2 on 6mm Clear ($\epsilon = 0.039$, S3)	Clear	6mm Clear	Multitech G ALU PRO Warm Edge Spacer	Argon (90%)	18 mm
ENERGY PERFORMANCE RATINGS							
U factor [W/m ² · K]		Solar Heat Gain Coefficient		Visible Transmittance			
1.65		0.53		0.70			
Air Leakage [L/s · m ²]				Energy Rating			
0.0				35			

Thermal performance and visual transmittance ratings certified to CSA A440.2:19 & NFRC 100-2017.

Ratings are determined for fixed set of environmental conditions and a specific product. LabTest

Certification Inc. agency does not recommend or warrant product for any specific use.

Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19

& NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales

et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit

pour une utilisation particulière.

NOTES:

*Represents the Glazing Option according to Listing Report (can be only 1 - 5 at time of this report).



Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Polishinterior S.C. Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland Email: maciek@polishinterior.com Tel: +48 502 24 88 94							
Energy Performance Results for RSL38F Fixed Window – PI-RSL38F-IG02 PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.039$, S2, $\epsilon = 0.039$, S5), Spacer: Multitech G ALU PRO Warm Edge Spacer							
No. of glazing layers	Glazing option no.	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	02*	CG Prem2 on 4mm Clear ($\epsilon = 0.039$, S2) CG Prem2 on 4mm Clear ($\epsilon = 0.039$, S5)	Clear	4mm Clear	Multitech G ALU PRO Warm Edge Spacer	Argon (90%)	18 mm
ENERGY PERFORMANCE RATINGS							
U factor [W/m ² · K]		Solar Heat Gain Coefficient		Visible Transmittance			
0.96		0.44		0.64			
Air Leakage [L/s · m ²]				Energy Rating			
0.0				44			

Thermal performance and visual transmittance ratings certified to CSA A440.2:19 & NFRC 100-2017.
Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

NOTES:

*Represents the Glazing Option according to Listing Report (can be only 1 - 5 at time of this report).



Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Polishinterior S.C.

Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland
Email: maciek@polishinterior.com Tel: +48 502 24 88 94

Energy Performance Results for RSL38F Fixed Window – PI-RSL38F-IG03

PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.039$, S2, $\epsilon = 0.039$, S5),
Spacer: Multitech G ALU PRO Warm Edge Spacer

No. of glazing layers	Glazing option no.	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	03*	CG Prem2 on 6mm Clear ($\epsilon = 0.039$, S2) CG Prem2 on 6mm Clear ($\epsilon = 0.039$, S5)	Clear	6mm Clear	Multitech G ALU PRO Warm Edge Spacer	Argon (90%)	16 mm

ENERGY PERFORMANCE RATINGS

U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance
0.95	0.43	0.63
Air Leakage [L/s · m ²]		Energy Rating
0.0		44

Thermal performance and visual transmittance ratings certified to CSA A440.2:19 & NFRC 100-2017.

Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.

Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

NOTES:

*Represents the Glazing Option according to Listing Report (can be only 1 - 5 at time of this report).



Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Polishinterior S.C. Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland Email: maciek@polishinterior.com Tel: +48 502 24 88 94							
Energy Performance Results for RSL38F Fixed Window – PI-RSL38F-IG04 PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.027$, S2, $\epsilon = 0.027$, S5), Spacer: Multitech G ALU PRO Warm Edge Spacer							
No. of glazing layers	Glazing option no.	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	04*	SN70S on 4mm Clear ($\epsilon = 0.027$, S2) SN70S on 4mm Clear ($\epsilon = 0.027$, S5)	Clear	4mm Clear	Multitech G ALU PRO Warm Edge Spacer	Argon (90%)	18 mm
ENERGY PERFORMANCE RATINGS							
U factor [W/m ² · K]		Solar Heat Gain Coefficient		Visible Transmittance			
0.95		0.27		0.49			
Air Leakage [L/s · m ²]				Energy Rating			
0.0				35			

Thermal performance and visual transmittance ratings certified to CSA A440.2:19 & NFRC 100-2017.
Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

NOTES:

*Represents the Glazing Option according to Listing Report (can be only 1 - 5 at time of this report).



Fenestration Certification Labels

Manufacturer: Polishinterior S.C.

Project No.: 21543
40.00.21543-6

Polishinterior S.C.

Address: Nad Drwina 10 hala D9, 30-741 Krakow, Poland
Email: maciek@polishinterior.com Tel: +48 502 24 88 94

Energy Performance Results for RSL38F Fixed Window – PI-RSL38F-IG05

PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.027$, S2, $\epsilon = 0.027$, S5),
Spacer: Multitech G ALU PRO Warm Edge Spacer

No. of glazing layers	Glazing option no.	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	05*	SN70S on 6mm Clear ($\epsilon = 0.027$, S2) SN70S on 6mm Clear ($\epsilon = 0.027$, S5)	Clear	6mm Clear	Multitech G ALU PRO Warm Edge Spacer	Argon (90%)	16 mm

ENERGY PERFORMANCE RATINGS

U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance
0.93	0.26	0.48
Air Leakage [L/s · m ²]		Energy Rating
0.0		35

Thermal performance and visual transmittance ratings certified to CSA A440.2:19 & NFRC 100-2017.

Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.

Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

NOTES:

*Represents the Glazing Option according to Listing Report (can be only 1 - 5 at time of this report).

