

Fenestration Certification Labels

Manufacturer: Parwood Door Products

Project No.: 22202

Report no.: 40.00.22202-3_Rev 0

Product Type 1 Label

 Evaluated to/Évalué pour: CSA 101/I.S.2/A440-17 CSA A440S1:19	Manufacturer: Parwood Door Products Address: 7550 Conrad Street, Burnaby, BC V5A 2H7, Canada Email: jason@parwood.ca, Tel: (236)-427-8604 Model No: EC778HD-D-4296-FP Side-Hinged Door Class LC – PG35 – Size tested: 1105 x 2460 mm (43.5 x 96.9 in) – Type SHD X Positive/ Negative ASD Design Pressure (DP) = 2400 Pa Water Penetration Resistance Test Pressure = 360 Pa Canadian Air Infiltration/ Exfiltration = A3 level
--	---

Legend:

Class LC

PG35

PG2400 (SI)

Size tested 1105 x 2460 mm

Size tested 43.5 x 96.9 in

Type SHD X

– Performance Class

– Performance Grade (IP)

– Performance Grade (SI)

– Maximum size tested (SI)

– Maximum size tested (IP)

– Product type – side-hinged door, hardware not tested

Fenestration Certification Labels

Manufacturer: Parwood Door Products

Project No.: 22202

Report no.: 40.00.22202-3_Rev 0

Parwood Door Products. Address: 7550 Conrad Street, Burnaby, BC V5A 2H7, Canada Email: jason@parwood.ca, Tel: (236) 427-8604							
Energy Performance Results for EC778HD-D-4296-FP Side-Hinged Door							
No. of glazing layers	Glazing option no.*	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ENERGY PERFORMANCE RATINGS							
U factor [W/m ² · K]	SOLAR HEAT GAIN COEFFICIENT		Visible Transmittance				
0.97	0.0		0.0				
Air Leakage [L/s · m ²]			Energy Rating				
0.4			N/A				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.

Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

