

SAMPLE MARKING LABEL

1. Performance Class and Performance Grade marking label:

Overall Rating Label

 Evaluated to/Évalué pour: AAMA/WDMA/CSA 101/I.S.2/A440-17 CSA A440S1-17	Manufacturer: Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367 Model No: EURC-7900SD-3,SB60(2)-3,CL16AR90TG OXXO PDV2MW Sliding Patio Door Class R – PG20 – Size tested: 4851 x 2724 mm (~191 x 107.2 in) – Type SD Positive/ Negative ASD Design Pressure (DP) = 1200 Pa Water Penetration Resistance Test Pressure = 180 Pa Canadian Air Infiltration/ Exfiltration = A3 Level
--	---

2. Energy Performance marking label:

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,SB60(2)-3,CL16AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	Solarban 60 on 3mm Clear ($\epsilon = 0.035$, S2)	Clear	Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	16.2 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.70	0.29	0.52				
Air Leakage [L/s · m²]		Energy Rating				
0.2		19				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,270(2)-3,CL-16AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, (ϵ = 0.035, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	Solarban 60 on 4mm Clear (ϵ = 0.035, S2)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	14.3 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.69	0.29	0.52				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		19				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,SB60(2)-4,IS20(4)-14AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.198$, S4), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	Solarban 60 on 4mm Clear ($\epsilon = 0.035$, S2) SunGuard IS20 on 4mm Clear ($\epsilon = 0.198$, S4)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	14.3 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.48	0.28	0.50				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		23				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,270(2)-4,i89(4)-14AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.149$, S4), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S2) i89 on 3mm Clear ($\epsilon = 0.149$, S4)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	14.3 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.45	0.26	0.49				
Air Leakage [L/s · m²]		Energy Rating				
0.2		23				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,366(2)-3,CL-16AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.02$, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	LoE ³ 366 on 3mm Clear ($\epsilon = 0.02$, S2)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	16.2 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.67	0.20	0.46				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		15				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,366(2)-4,CL-14AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, (ϵ = 0.02, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	LoE ³ 366 on 4mm Clear (ϵ = 0.02, S2)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	14.3 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.66	0.20	0.46				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		15				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,366(2)-4,CL-14AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S2)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	15.9 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.72	0.27	0.50				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		18				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,270(2)-4,CL-14AR90TG PVC frame; Double glazed system, Argon (90%) gap fill, (ϵ = 0.035, S2), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
2	LoE ² 270 on 4mm Clear (ϵ = 0.035, S2)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	14.3 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.71	0.26	0.49				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		17				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,270(2)-3,CL-3,270(5)-11AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.035$, S5), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S2) LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S5)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	11.1 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.22	0.23	0.39				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		26				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,270(2)-4,CL-4,270(5)-10AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.035$, S5), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 4mm Clear ($\epsilon = 0.035$, S2) LoE ² 270 on 4mm Clear ($\epsilon = 0.035$, S5)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	9.5 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.29	0.22	0.38				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		24				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,270(2)-3,270(4)-3,i89(6)-11AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.035$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S2) LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S4) i89 on 3mm Clear ($\epsilon = 0.149$, S6)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	11.1 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.14	0.20	0.38				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		26				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,270(2)-4,270(4)-5,i89(6)-10AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.035$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 4mm Clear ($\epsilon = 0.035$, S2) LoE ² 270 on 4mm Clear ($\epsilon = 0.035$, S4) i89 on 5mm Clear ($\epsilon = 0.149$, S6)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	9.5 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.20	0.20	0.37				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		25				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,180(2)-3,180(4)-3,i89(6)-11AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.068$, S2, $\epsilon = 0.068$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE 180 on 3mm Clear ($\epsilon = 0.068$, S2) LoE 180 on 3mm Clear ($\epsilon = 0.068$, S4) i89 on 3mm Clear ($\epsilon = 0.149$, S6)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	11.1 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.17	0.39	0.49				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		37				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,180(2)-4,180(4)-5,i89(6)-10AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.068$, S2, $\epsilon = 0.068$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE 180 on 4mm Clear ($\epsilon = 0.068$, S2) LoE 180 on 4mm Clear ($\epsilon = 0.068$, S4) i89 on 5mm Clear ($\epsilon = 0.149$, S6)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	9.5 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.23	0.37	0.48				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		34				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use.
Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-3,270(2)-3,180(4)-3,i89(6)-11AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.068$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S2) LoE 180 on 3mm Clear ($\epsilon = 0.068$, S4) i89 on 3mm Clear ($\epsilon = 0.149$, S6)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	11.1 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.16	0.23	0.43				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		27				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-4,270(2)-4,180(4)-5,i89(6)-10AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S2, $\epsilon = 0.068$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 4mm Clear ($\epsilon = 0.035$, S2) LoE 180 on 4mm Clear ($\epsilon = 0.068$, S4) i89 on 5mm Clear ($\epsilon = 0.149$, S6)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	9.5 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.21	0.23	0.42				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		26				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-6,GRY-3,270(3)-3,i89(6)-10AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, ($\epsilon = 0.035$, S4, $\epsilon = 0.149$, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 3mm Clear ($\epsilon = 0.035$, S4) i89 on 3mm Clear ($\epsilon = 0.149$, S6)	Clear	3mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	9.5 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.37	0.17	0.22				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		19				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).

Euroclad Windows and Doors Address: 2490 Ross Road, West Kelowna BC V1Z 1M1, Canada Email: steve@eurocladsystems.com, Tel: (250) 769-0367						
Energy Performance Results for OXXO PDV2MW Sliding Patio Door – EURC-7900SD-6,GRY-4,270(3)-5,i89(6)-8AR90TG PVC frame; Triple glazed system, Argon (90%) gap fill, (ε = 0.035, S4, ε = 0.149, S6), Spacer: Technoform Glass Insulation (TGI) Spacer Bar						
No. of glazing layers	Glass surface emissivity with Low-E coating	Tint description	Glass type(s)	Spacer type(s)	Gap fill(s)	Gap width(s)
3	LoE ² 270 on 4mm Clear (ε = 0.035, S4) i89 on 5mm Clear (ε = 0.149, S6)	Clear	4mm Clear	Technoform Glass Insulation (TGI) Spacer Bar	Argon (90%)	7.9 mm
ENERGY PERFORMANCE RATINGS						
U factor [W/m ² · K]	Solar Heat Gain Coefficient	Visible Transmittance				
1.43	0.17	0.21				
Air Leakage [L/s · m ²]		Energy Rating				
0.2		18				

Thermal performance and visual transmittance ratings certified to CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. Ratings are determined for fixed set of environmental conditions and a specific product. LabTest Certification Inc. agency does not recommend or warrant product for any specific use. Les taux de performance thermique et de transmission visuelle certifiées selon la norme CSA A440.2:19/CSA A440.3:19 & NFRC 100-2017. L'évaluation est déterminée pour un ensemble fixe de conditions environnementales et un produit spécifique. LabTest Certification Inc. ne recommande pas et ne recommande aucun produit pour une utilisation particulière.

**NOTES:**

*Represents the Glazing Option according to Listing Report (can be only 1 - 18 at time of this report).